

Anqing Yipak Packaging Material Co.Ltd

TECHNICAL DATA SHEET

Heat Sealing Sterilization Flat&Gusseted Pouches





Sterilization Flat Pouch

Item No.: YFP

 $\begin{array}{ccc} \text{Sizes: 75mm} \times 250 \text{mm} & 150 \text{mm} \times 300 \text{mm} \\ & 100 \text{mm} \times 250 \text{mm} & 150 \text{mm} \times 400 \text{mm} \\ & 100 \text{mm} \times 300 \text{mm} & 210 \text{mm} \times 350 \text{mm} \end{array}$

 $150mm \times 250mm \\$

Sterilization Gussetted Pouch

Item No.: YGP

Size: $100\text{mm} \times 30\text{mm} \times 300\text{mm}$ $250\text{mm} \times 50\text{mm} \times 500\text{mm}$ $150\text{mm} \times 40\text{mm} \times 300\text{mm}$ $300\text{mm} \times 50\text{mm} \times 600\text{mm}$ $150\text{mm} \times 40\text{mm} \times 400\text{mm}$ $450\text{mm} \times 60\text{mm} \times 600\text{mm}$ $200\text{mm} \times 40\text{mm} \times 400\text{mm}$ $180\text{mm} \times 95\text{mm} \times 380\text{mm}$

Features:

- Material: medical dialysis paper(60g/m² or 70g/m² + composite film (52 microns CPP/PET film)
- Printed with double sterilization indicators for ethylene oxide and steam vapor processes
- Can be sealed by thermal sealing machines
- See-through the sterilized medical device by transparent compound film, avoiding errors
- 3 aligned sealed lines, effectively avoiding crack
- Minimized printed area in and between the sealed layer of paper and film to prevent any instrument contamination
- Clean Peel-easy separate the film from the paper with no shatters
- If sterilization proceeded, it will turn black from initial blue based on steam sterilization method, and will turn yellow from initial pink based on the EO sterilization method
- Lead-free ink, Latex-free and no toxic heavy metals
- The wide range of sizes provides users the greatest flexibility for packaging needs
- Pouches are notched at both ends for ease of use
- Consistent with the European standard: EN ISO 11607-1 EN 868 part-3 and part-5 EN 11140-1 EN 980
- Keep stored in the dark at room temperature 15°C~30°C and 50% relative humidity, avoid to contact with corrosive gases.
- Shelf time: Since the date of production 5 years