

# Dry Bath

## SCI120-S

### Dry bath








#### Features

- A wide range of temperature control up to 120°C
- Timer function support is available
- Various types of optional blocks are available
- Overheating protection
- Lid for protection and heat preservation



#### Specifications

	SCI120-S
Functions	Heating
Temperature range	Room temp.-120°C
Temperature control accuracy	± 0.5°C
Temperature uniformity	± 0.5°C
Max. heating rate	5.5°C/min
Timer	0min-99h59min
Screen	LED
Overheating protection	140°C
Adapter block material	aluminum
Voltage, Frequency	100-120V/220-240V,50Hz/60Hz
Power	160W
Dimension[WxDxH ]	175 x 290 x 85mm
Weight	3kg

Cat.No.	Block types	Capacity	Diameter Depth
18900218		0.2mLx54	6.4mm 15mm
18900219		0.5mLx40	8.2mm 26.4mm
18900253 (1.5mL) 18900220 (2mL)		1.5mLx40 2mLx40	11mm 34.7mm
18900221		5/15mLx28	17mm 48mm
18900222		50mLx8	29.8mm 48mm
18900224		0.2mL+0.5mL+1.5/2mL 18+18+18	-
18900223		96 or 384 well plate	-



Adapter block selection



Overheating protection



Timer



LED display

# Dry Baths



The SCILOGEX Mini Dry baths are portable and compact and useful for rapid and uniform heating of biological samples, in applications like preservation, denaturation of nucleic acids and proteins and many other applications.

## SCI-100MiniHCL SCI-100MiniHC SCI-100MinH Dry Bath

### Features:

- Lightweight
- LCD displays temperature and time.
- Rapid calibration support
- Overheating protection.
- Optional blocks with different capacities are available.
- Safe and stable.
- USB interface to save the data
- Mini HCL100 with hot lid to preserve the generated heat.

Cat.NO.	Block types	Capacity	Diameter x depth
18900414		0.2mlx40	6.4x20 mm
18900415		0.5mlx24	8.2x28.4mm
18900416		1.5mLx15	11.2x31mm
18900428		2mlx15	11x31mm
18900417		5mLx6	17x31mm
18900426		15mlx4	16.4x45mm
18900427		50mlx2	29x45mm

### Specifications

	SCI-100MiniHCL	SCI-100MiniHC	SCI-100MiniH0
Display	LCD	LCD	LCD
Temperature setting range[°C]	0-100	0-100	25-100
Temperature range [°C]	Room temperature-23~100	Room temperature-23~100	Room temperature+5~100
Temperature control accuracy[°C]	± 0.5	± 0.5	± 0.5
Temperature display accuracy[°C]	0.1	0.1	0.1
Minimum time taken for heating(25°C-100°C )	≤20min	≤20min	≤20min
Minimum time for cooling ( 20°C-0°C )	≤25min	≤25min	/
Max. Heating Rate	8° C /min	8° C /min	6.5° C /min
Max. Cooling Rate	3° C /min	3° C /min	/
Time setting range	0-999min/0-999sec	0-999min/0-999sec	0-999min/0-999sec
No. of programs in memory	9(2steps for each )	9(2steps for each )	9(2steps for each )
Rapid calibration	Support	Support	Support
USB interface	Support	Support	Support
Error code reminder	Support	Support	Support
External dimension [mm]	110x162x140	110x162x140	110x162x140
Overall weight [kg]	≤1	≤1	≤1
Power supply	DC 12V,100-240V, 50/60Hz	DC 12V,100-240V, 50/60Hz	DC 12V,100-240V, 50/60Hz
Power[w]	60	60	60
Operating temperature[°C]	+10-40	+10-40	+10-40
Operating humidity [% RH]	≤80	≤80	≤80