

GW4060



LABORATORY GLASSWARE WASHER WITH DRYING SYSTEM
BASIC LINE - GLASSWARE WASHER 60 CM WITH DRYING SYSTEM
[Download PDF](#)

- ✓ washing up to 95°C - antibacterial thermal disinfection
- ✓ programs: 9 default + 6 custom
- ✓ microprocessor programmable electronic control
- ✓ serial port RS232 for connection to external printer or PC
- ✓ forced hot air drying system with air filter 98% DOP
- ✓ alkaline powder detergent dispenser
- ✓ peristaltic pump for acid liquid neutralizer
- ✓ possibility of installing up to 2 additional peristaltic pumps
- ✓ washing chamber and internal door in AISI 316L stainless steel
- ✓ external panels made of AISI 304 stainless steel
- ✓ n. 2 independent washing levels through telescopic guides
- ✓ external dimensions LxDxH: 600 x 600 x 850 mm
- ✓ internal working dimensions LxDxH: 525 x 490 x 570 mm
- ✓ incorporated water softener with salt sensor
- ✓ cold water and demineralized water connections
- ✓ electronic door lock system for user safety
- ✓ electrical connection: 3/N/PE 400 V - 50 Hz - 7 kW max
- ✓ single phase version available: 1/N/PE 230 V - 50 Hz - 2,8 kW max (GW4060-1)
- ✓ 60 Hz version available
- ✓ without trolleys

Smeg S.p.A. Via Leonardo Da Vinci, 4 - 42016 Guastalla (RE) Italy - P. IVA 01555030350
Phone +39 0522 8211 - fax +39 0522 821453 - service.instruments@smeg.it

